

O United Rentals

Shoring, Propping & Fluid Solutions



shorehire.com.au

C

1300 746 734

SYDNEY

360 Edgar Street, Condell Park, NSW, 2200

SUNSHINE COAST

16-24 Fred Chaplin Circuit, Bells Creek, QLD, 4551

BRISBANE

27 Transport St, Yatala, QLD, 4207

NEWCASTLE

18 Yilen Close, Beresfield, NSW, 2322

MELBOURNE WEST

1 Oban Court, Laverton North, VIC, 3026

MELBOURNE EAST

40 Argoon Road, Healesville, VIC, 3026

ADELAIDE

34 Wingfield Road, Wingfield, SA, 5013

In support of our policy of continuous product development we reserve the right to change materials and specification without notice. Drawings, where shown may not be to scale.

Dimensions are metric and size are approximate. Where possible specification sheets are made available on our website. All products should be installed and used in accordance with manufacturer's instruction provided. Warning: products may be subject of registered designs and patents. Refer to our websites for terms and conditions. Every effort has been made to ensure accuracy of content. However, no liability will be met by United Rentals or its suppliers for any errors or omissions. Product data and information is not binding.

All brands and logos are registered trademarks and are subject to copyright laws. No part of this document may be reproduced without the consent of United Rentals.



Work United

MULTI LOADER 3.0 FX

COMPACT. POWERFUL. JOB-SITE READY.

When space is tight and loads are heavy, the 3.0 FX delivers precision, performance and adaptability.

Built for demanding environments, the Multi Loader 3.0 FX offers a rated capacity of 3,000 kg in a highly compact tracked carrier. Featuring extendable support beams and a 360° swivel platform, it's engineered for manoeuvrability, site-access ease and heavy-duty lifting in confined or challenging conditions.



KEY BENEFITS

- Despite its compact size, the 3.0 FX handles up to 3000 kg of load.
- Precision control & versatility
 The swivel platform with 15 positions makes load orientation easy and efficient.
- Adaptable support system

 Telescopic support beams extend longitudinally or laterally for extra stability when carrying large or awkward loads.
- Quiet, clean operation


 A fully electric drive system with non-marking tracks means it's suited for both indoor and outdoor use, with minimal disturbance.
- Efficient uptime

 Removable battery pack supports up to 7 hours of operation; rapid recharge times keep downtime low.

FEATURES SUMMARY

TECHNICAL DATA	ML 3.0 FX
Rated capacity	3000kg
Max gradient	45°
Height	540mm
Dimensions	790mm W x 1780mm L
Track width	1300mm
Ground clearance	40mm
Max speed	4.2km/h
Gross weight	760kg
Controller	remote radio control
Fully electric drive	AC Motors (2 x 5.3KW)
Tracks	non-marking
Swivel platform	360° with 15 positions
Platform stability	extendable telescopic support beams
Operation hours	up to 7 hours (ours has the larger battery)
Hazard lights	front & rear
Alarm	automatic tilt with speed reduction





TYPICAL APPLICATIONS & USE-CASES

- Transporting heavy equipment and materials

 Across site, especially where access is limited or terrain is tricky.
- Indoor and outdoor use

 Thanks to quiet, zero-emissions electric drive and non-marking tracks, it's ideal for
- Confined spaces or steep gradients

 With a 45° gradient rating and compact dimensions, it climbs and maneuvers where many machines struggle.
- Rental applications

 Plant hire fleets, building refurbishments, industrial sites, utilities and plant relocation tasks.

SAFETY & RENTAL-READY FEATURES

Certified

To Australian stanards

sensitive floor surfaces.

Electric drive

Reduces noise and fumes for safe indoor use or semi-enclosed spaces.

Non-marking tracks

Protect finished surfaces

Remote control

Simplifies operator positioning and safe load handling.

Telescopic support beams

Ensure stability during load manoeuvres; tilt alarm feature adds safety margin.